

This Manufacturer Certification Statement is provided to certify that the highlighted exterior door slabs listed below, when installed properly, meet the specific energy efficiency criteria to qualify for a tax credit under the Tax Relief, Unemployment Insurance Reauthorization and Job Creation Act of 2010. Please visit www.energystar.gov/taxcredit for more information. Product must be purchased and installed from 1/1/2011 to 12/31/2011.

Taylor Building Products stipulates compliance with NFRC requirements to the standards listed below, using the most current NFRC approved spectral data.

85222.18-201-45 ATI Expires 8/28/2012

Revised 12/03/10

Thermal Performance Test

NFRC 100 - Procedure for Determining Fenestration Product U-Factors

NFRC 200 - Procedure for Determining Fenestration Product SHGC and VT

NFRC 500 - Procedure for Determining Fenestration Product Condensation Resistance Values

TAYLOR STEEL EDGE DOOR

EMBOSSSED PANEL U-FACTOR 0.18, SHGC 0.01

Glass/Door Type	1/2" Glass, Clear, Air	1/2" Glass, Clear, Air	1/2" Glass, Low E, Air	1/2" Glass, Low E, Air	1/2" Glass, Low E, Argon	1/2" Glass, Low E, Argon
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
1/4 Lite	0.2	0.03	0.2	0.02	0.2	0.02
1/2 Lite	0.32	0.2	0.29	0.11	0.27	0.11
3/4 Lite	0.38	0.29	0.33	0.16	0.31	0.16
Full Lite	0.4	0.32	0.35	0.18	0.32	0.17

Glass/Door Type	1" Glass, Clear, Air	1" Glass, Clear, Air	1" Glass, Low E, Air	1" Glass, Low E, Air	1" Glass, Low E, Argon	1" Glass, Low E, Argon
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
1/4 Lite	0.2	0.03	0.2	0.02	0.2	0.02
1/2 Lite	0.31	0.2	0.26	0.11	0.25	0.11
3/4 Lite	0.36	0.29	0.3	0.16	0.28	0.16
Full Lite	0.38	0.32	0.32	0.17	0.30	0.17

Glass/Door Type	1" Decorative, Air	1" Decorative, Air	1" Decorative, Low E, Air	1" Decorative, Low E, Air	1" Decorative, Low E, Argon	1" Decorative, Low E, Argon
	U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
1/4 Lite	0.2	0.05	0.2	0.03	0.19	0.03
1/2 Lite	0.27	0.16	0.25	0.09	0.24	0.09
3/4 Lite	0.31	0.24	0.28	0.13	0.26	0.13
Full Lite	0.32	0.26	0.29	0.15	0.27	0.15

NOTES: All Low-E glass ratings based on Low E with an (e = 0.044 or better), SHGC for clear glass units is without grids.

1/4, 1/2, 3/4 lites values are from embossed panel data, Full lite data is from flush panels

Full testing information available upon request

Meets or exceeds Energy Star® Requirements for Doors

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

K R B

Kevin R. Bulow
Product and R&D Manager
Taylor Building Products
2/3/2011

